


**Product Code:**

FT-20T-6.5A1W152


**Picture:**

**Specification:**

Resonant frequency	(KHz)	6.5±0.5
Resonant impedance	(Ω)	≤400
Capacitance at 1KHz	(pF)	15000±30%
Metal plate diameter (mm) (D)	(mm)	φ 20.0±0.2
Ceramic plate diameter (mm) (d)	(mm)	φ 15.0±0.4
sTotal thickness (mm) (T)	(mm)	0.4±0.05
Metal plate thickness (mm) (t)	(mm)	0.2±0.03
Metal material		Brass
RoHS		Yes

Test basic state:

Temp(20±2℃) , Humidity(40~70%RH) , Air pressure(860~1060hPa).

**Environment Test:**

ITEM	TESTING CONDITION	RECOVERY CONDITION
Humidity	40±2℃, 93(+2/-3)%RH, 96HRS	2 hour recovery under normal temp.
Temp.	-10±2℃, 30minutes room temp. 15 minutes +70±2℃, 30 minutes room temp. 15 minutes 5 cycles	2 hour recovery under normal temp.
High temp.	+70±2℃, Not less than 30min	Measurement under high temp.
Low temp.	-10±2℃, Not less than 30min	Measurement under low temp.

Evaluation standard :

Change requirement on electrical performance:

Resonant frequency ±20%, Free capacitance ±30%

**Dimensions:**
